



Wireless Hand-held Barcode Scanner W40-21

Feature

- **Excellent Code Reading Performance**
Built-in reading engine with the world's leading decoding algorithm, W40-21 can easily read all kinds of bent, stained, blurred and other low-quality barcodes, even on-screen codes
- **Powerful Battery Life**
Lithium battery with large capacity, support low power mode, significantly improve the product range, meet all kinds of high load applications.
- **Plug and play, stable and convenient wireless communications**
No need for installation, simple matching, easy to learn and easy to use, plug and play. 2.4 G and bluetooth compact design, meet the demand of different applications.
- **Compatible Multiple Platforms**
Fully compatible with Windows,Android,Linux systems.

Scenarios

Retail, hospital, warehousing,inventory management, electronic industry production traceability management, light industry production traceability management, warehousing logistics management

W40-21/Wireless Hand-held Barcode Scanner

Performance	Image Sensor	640*480	
	Symbologies	2D	PDF417, Data Matrix, QR Code, Micro QR Code
		1D	Code 128, EAN-13, EAN-8, Code 39, UPC-A, UPC-E, Codabar, Interleaved 2 of 5, ITF-6, ITF-14, ISBN, Code 93, UCC/EAN-128, GS1 Databar, Matrix 2 of 5, Code 11, Industrial 25, Standard 25, ISSN, Plessey, MSI-Plessey, AIM 128
	Scan Precision	≥5mil	
	Depth of View	EAN-13	50mm~260mm (13mil)
		Code 39	50mm~115mm (5mil)
		QR Code	30mm~170mm (15mil)
	Scan Angle	Pitch: ±60°; Roll: 360°; Skew: ±60°	
	PCS	≥25%	
	Data Transmission	2.4G, Bluetooth BLE/HID/SPP, Wired USB	
	Transmission Distance	50m (Open Empty Area)	
	Mechanic/	Size	160*95*65mm'
Electrical	Weight	190g	
	Notification	Sound、LED and Vibration	
	Battery	2000mAH	
	Use time per charge	14 hours (EAN13 barcode, read and transmit data once every 5 seconds)	
	Recharging Time	2 hours	
Environmental	Operation Temperature	-20℃ to 50℃	
	Storage Temperature	-40℃ to 70℃	
	Operation Humidity	5%~95% (non-condensing)	
	ESD	±8 KV (Air Discharge); ±4KV (Contact Discharge)	
	Drop	1.2m	
	Housing IP level	IP42	
Certification	FCC Part15 Class B, CE EMC Class B, BIS		

V1.0



Contact:

Shenzhen Edoo-IoT Technology Co., Ltd.

Tel: +86-135-3782-5290(WeChat)

Website: www.edoo-iot.com

Add: Room 302, Bldg U6, U8 Intelligent Manufacturing Park, Hancheng Blvd, Gushu, Xixiang, Bao'an District, Shenzhen
Shenzhen